



固 體 電 子 有 限 公 司 SOLITRONICS ENGINEERING LTD.

1515, STAR HOUSE, 3, SALISBURY ROAD., KOWLOON, HONG KONG S.A.R. CHINA
Tel: (852)-2730-8145 Fax: (852)-2730-3245 E-mail: info@solitronics.com

12th December, 2004

PL-NI09-LED-V2

PRICE LIST OF NI-09 SERIES SNAP-FIT LED INDICATOR FOR 9Ømm PANEL CUT-OUT

1. Snap-fit Self-flashing LED-Indicator for 12V & 24V DC only

Data sheet Solico-NI09-LED-01

Solitronics P/N	Voltage & Current	Lens-colour	Led Colour	Typ. mcd@20mA	Ex-works per pc
SEL-NI09-LED-RF-12	12-14V DC only 20mA Peak	Red	High-Bright Red 660nm	390 mcd Min.	US\$0.75
SEL-NI09-LED-GF-12	12-14V DC only 20mA Peak	Green	High-Bright Green 569nm	180 mcd Min.	US\$0.80
SEL-NI09-LED-AF-12	12-14V DC only 20mA Peak	Amber	High-Bright Yellow 595nm	570 mcd Min.	US\$0.80
SEL-NI09-LED-RF-24	24-30V DC only 20mA Peak	Red	High-Bright Red 660nm	390 mcd Min.	US\$0.75
SEL-NI09-LED-GF-24	24-30V DC only 20mA Peak	Green	High-Bright Green 569nm	180 mcd Min.	US\$0.80
SEL-NI09-LED-AF-24	24-30V DC only 20mA Peak	Amber	High-Bright Yellow 595nm	570 mcd Min.	US\$0.80

2. Snap-fit LED indicator for 12V AC/DC & 24V AC/DC

Data sheet SEL-NI09-LED-02-D1

Solitronics P/N	Voltage & Current	Lens-Colour	Led Colour	Typ. mcd@3.0mA	Ex-works per pc.
SEL-NI09-LED-R1-12S	12-14V AC/DC 8-15mA	Red	Super-Bright Red 660nm	1007-1890 mcd	US\$0.50
#SEL-NI09-LED-G1-12S	12-14V AC/DC 8-15mA	Green	#Super-Bright Green 525nm	1080-2025 mcd	US\$1.80
SEL-NI09-LED-G1-12D	12-14V AC/DC 8-15mA	Green	Diffused Hi-Bright Green 565nm	106-199 mcd	US\$0.50
SEL-NI09-LED-A1-12S	12-14V AC/DC 8-15mA	Amber	Super-Bright Yellow 586nm	960-1800 mcd	US\$0.55
SEL-NI09-LED-A1-12D	12-14V AC/DC 8-15mA	Amber	Diffused Hi-Bright Yellow 585nm	306-574 mcd	US\$0.52
#SEL-NI09-LED-B1-12S	12-14V AC/DC 8-15mA	Blue	#Super-Bright Blue 470nm	900-1687 mcd	US\$1.90
SEL-NI09-LED-R1-24S	24-30V AC/DC 6-10mA	Red	Super-Bright Red 660nm	757-1262 mcd	US\$0.50
#SEL-NI09-LED-G1-24S	24-30V AC/DC 6-10mA	Green	#Super-Bright Green 525nm	810-1350 mcd	US\$1.80
SEL-NI09-LED-G1-24D	24-30V AC/DC 6-10mA	Green	Diffused Hi-Bright Green 565nm	80-132 mcd	US\$0.50
SEL-NI09-LED-A1-24S	24-30V AC/DC 6-10mA	Amber	Super-Bright Yellow 586nm	720-1200 mcd	US\$0.55
SEL-NI09-LED-A1-24D	24-30V AC/DC 6-10mA	Amber	Diffused Hi-Bright Yellow 585nm	230-382 mcd	US\$0.52
#SEL-NI09-LED-B1-24S	24-30V AC/DC 6-10mA	Blue	#Super-Bright Blue 470nm	657-1125 mcd	US\$1.90

3. Snap-fit 130V-230V AC LED indicator

Data sheet SEL-NI09-LED-03-D1

Solitronics P/N	Voltage & Current	Red	Colour	Typ mcd@3.0mA	Ex-works per pc.
SEL-NI09-LED-R1-130S	130V AC only 3.0mA	Green	Super-Bright Red 660nm	Typical 370 mcd	US\$0.55
#SEL-NI09-LED-G1-130S	130V AC only 3.0mA	Green	#Super-Bright Green 525nm	Typical 405 mcd	US\$1.85
SEL-NI09-LED-A1-130S	130V AC only 3.0mA	Amber	Super-Bright Yellow 586nm	Typical 360 mcd	US\$0.60
SEL-NI09-LED-A1-130D	130V AC only 3.0mA	Amber	Diffused Hi-Bright Yellow 585nm	Typical 120 mcd	US\$0.57
#SEL-NI09-LED-B1-130S	130V AC only 3.0mA	Blue	#Super-Bright Blue 470nm	Typical 337 mcd	US\$1.95
SEL-NI09-LED-R1-230S	230V AC only 2.0mA	Red	Super-Bright Red 660nm	Typical 370 mcd	US\$0.55
#SEL-NI09-LED-G1-230S	230V AC only 2.0mA	Green	#Super-Bright Green 525nm	Typical 405 mcd	US\$1.85
SEL-NI09-LED-A1-230S	230V AC only 2.0mA	Green	Super-Bright Yellow 586nm	Typical 360 mcd	US\$0.60
SEL-NI09-LED-A1-230D	230V AC only 2.0mA	Amber	Diffused Hi-Bright Yellow 585nm	Typical 120 mcd	US\$0.57
#SEL-NI09-LED-B1-230	230V AC only 2.0mA	Amber	#Super-Bright Blue 470nm	Typical 337 mcd	US\$1.95

Note: Types with # mark indicates GAN LED which is sensitive to electrostatic electricity.

When used in environment susceptible to static electricity the use of a 470K bleeding resistor across terminals of the indicator is recommended. All specifications and offers are subject to change without notice.