



SOLITRONICS ENGINEERING LTD.

TEL: (852)-2730-8145

FAX: (852)-2730-3245

E-mail: info@solitronics.com

SUB-MINIATURE LAMP SPECIFICATIONS

Date: 3rd February 2001

Telephone Slide Lamps

Data Sheet:

SEL-SS-1012

T-4.5	T-4.6	T-5.5K	T-5.5	T-6.8 (DIN)	PSB
Fig. A	Fig. B	Fig. C	Fig. D	Fig. E	Fig. F

* Note: All dimensions in mm.

	Volts (V)	AMPS (A)	Avg. Lumen	Avg. Life (Hrs.)	Filament Shape	T-4.5 Fig. A	T-4.6 Fig. B	T-5.5K Fig. C	T-5.5 Fig. D	T-6.8(DIN) Fig. E	PSB Fig. F
1	6.0	0.020	0.17	10,000	C-2V	450620	460620	520620	550620	680620	
2	6.0	0.040	0.60	10,000	C-2V	450640	460640	520640	550640		
3	6.0	0.050	0.70	10,000	C-2V					680650	
4	6.0	0.100	2.20	10,000	C-2V					6806100	
5	6.0	0.140	1.52	20,000	C-2V						6PSB
6	6.0	0.200	6.00	10,000	C-2V					6806200	
7	12.0	0.020	0.40	10,000	C-2V	451220	461220	521220	551220	681220	
8	12.0	0.040	0.80	10,000	C-2V	451240	461240	521240	551240		
9	12.0	0.050	1.60	10,000	C-2V	451250	461250	521250	551250		
10	12.0	0.050	2.00	10,000	C-2V					681250	
11	12.0	0.100	4.00	10,000	C-2V			5212100	5512100		
12	12.0	0.100	5.50	10,000	C-2V					6812100	
13	12.0	0.170	4.45	12,000	C-2F						12PSB
14	24.0	0.020	0.70	10,000	C-2F	452420	462420	522420	552420	682420	
15	24.0	0.030	1.40	10,000	C-2F	452430	462430	522430	552430		
16	24.0	0.040	2.70	10,000	C-2F	452440	462440	522440	552440	682440	
17	24.0	0.050	3.40	10,000	C-2F	452450	462450	522450	552450	682450	
18	24.0	0.073	6.35	10,000	C-2F						24PSB
19	28.0	0.020	0.95	10,000	C-2F			522820	552820		
20	28.0	0.040	2.40	10,000	C-2F					682840	
21	28.0	0.040	3.30	5,000	C-2F				552840		28PSB
22	28.0	0.050	4.00	10,000	C-2F			522850	552850		
23	30.0	0.020	1.00	10,000	C-2F	453020	463020	523020	553020		
24	30.0	0.040	3.60	10,000	C-2F	453040	463040	523040	553040	683040	
25	30.0	0.050	4.40	10,000	C-2F			523050			
26	32.0	0.033	4.20	20,000	C-2F	453233	463233	523233	553233		
27	36.0	0.020	1.30	10,000	C-2F	453620	463620	523620	553620	683620	
28	36.0	0.040	4.70	10,000	C-2F					683640	
29	36.0	0.050	5.86	10,000	C-2F				553650	683650	
30	48.0	0.020	1.80	5,000	CC-2F	454820	464820	524820	554820	684820	
31	48.0	0.025	2.60	5,000	CC-2F				554825	684825	
32	48.0	0.030	3.10	5,000	CC-2F	454830	464830	524830	554830		
33	48.0	0.040	4.30	5,000	CC-2F					684840	
34	48.0	0.050	4.85	5,000	CC-2F					684850	
35	48.0	0.053	7.00	7,500	CC-2F						48PSB
36	60.0	0.020	2.00	5,000	CC-2F	456020	466020	526020	556020	686020	
37	60.0	0.040	8.00	5,000	CC-2F					686040	
38	60.0	0.050	7.07	7,500	CC-2F						60PSB
39	70.0	0.020	3.00	5,000	CC-2F				557020	687020	
40	120.0	0.025	4.57	10,000	SPCL						120PSB