





SE-SFC-1-1001

## SUB-MINIATURE LAMPS


**T-1 Wire Terminal  
(Fig. A)**




**T-1 Sub-Midget  
Flange  
(Fig. B)**



**T-1 Bi-pin (1.27)  
(Fig. C)**



**T-1 European Bi-pin  
(2.54)  
(Fig. D)**



### T-1 Sub-Miniature Lamps

| Volts | Amps  | MSCP      | Avg. Life (Hrs.) | Filament Shape | LAMP No.    |                 |                    |                    |
|-------|-------|-----------|------------------|----------------|-------------|-----------------|--------------------|--------------------|
|       |       |           |                  |                | WT (Fig. A) | S.M.F. (Fig. B) | BP (1.27) (Fig. C) | BP (2.54) (Fig. D) |
| 3.0   | 0.015 | 0.020 NOM | 5,000            | C-2R           | 7205        | 7229            | 3229               | E315               |
| 3.0   | 0.060 | 0.030     | 100,000          | C-2R           | 7207        | 7231            | 7260               | E306               |
| 5.0   | 0.021 | 0.034     | 10,000           | C-2R           | 6022        | 8022            | 7022               | E502               |
| 5.0   | 0.030 | 0.030     | 75,000           | C-2R           | 7210        | 7234            | 7263               | E503               |
| 5.0   | 0.060 | 0.030     | 100,000          | C-2R           | 680         | 682             | 7680               | E506               |
| 5.0   | 0.060 | 0.050     | 100,000          | C-2R           | 683         | 685             | 7683               | E556               |
| 5.0   | 0.075 | 0.090     | 25,000           | C-2R           | 713         | 714             | 7714               | E507               |
| 5.0   | 0.115 | 0.150     | 40,000           | C-2R           | 715         | 718             | 7715               | E515               |
| 10.0  | 0.027 | 0.100     | 10,000           | C-2F           | 7218        | 7240            | 8095               | E102               |
| 12.0  | 0.030 | 0.100     | 25,000           | C-2V           | D123        | D123F           | D123B              | E123               |
| 12.0  | 0.060 | 0.150     | 16,000           | C-2F           | 7219        | 32              | 8097               | E126               |
| 14.0  | 0.040 | 0.140     | 16,000           | C-2V           | 23          | 22              | 22F                | E144               |
| 18.0  | 0.026 | 0.150     | 16,000           | C-2F           | 7220        | 7241            | 8099               | E182               |
| 28.0  | 0.024 | 0.150     | 16,000           | CC-2F          | 6838        | 6839            | 7839               | E280               |